

## VM-1110xI

1:10 Balanced Mono Audio Distribution Amplifier



The VM-1110xl is a high-performance distribution amplifier for balanced mono audio signals on XLR connectors. It can also be configured as a 1:5 distribution amplifier for stereo balanced audio signals

## **FEATURES**

Level (Gain) Controls

Dual Mode - Configure as 1:10 (mono) or 1:5 (stereo) DA

S/N Ratio - 89.3dB

Standard 19" Rack Mount Size - 1U



## TECHNICAL SPECIFICATIONS

INPUTS: 2 balanced stereo audio,  $+4dBu/50k\Omega$  on XLR (F) connectors

OUTPUTS: 10 balanced stereo audio, +4dBu/50Ω on XLR (M) connectors

MAX. OUTPUT

LEVEL:

23.8Vpp

BANDWIDTH (-3dB): >100kHz

S/N RATIO: 89.3dB

CROSSTALK: -78dB

CONTROLS: Level (x2): -0.7dB to +5.1dB, mode selector switches

COUPLING: AC (input); DC (output)

AUDIO THD + NOISE: 0.081%

AUDIO 2nd 0.006%

HARMONIC:

POWER 230V AC, (115V AC USA), 6VA

CONSUMPTION:

INCLUDED ACCESSORIES:

Power cord

Product Dimensions 19" x 7.20 x 1U (43.6cm x 18.30cm x 4.36cm) W, D, H

Product Weight 2.8kg (6.2lbs) approx

Shipping Dimensions 55.00cm x 27.60cm x 10.70cm (21.65" x 10.87" x 4.21") W, D, H

Shipping Weight 3.6kg (8.0lbs) approx

